

HDS Seismic Isolator Series


Loading Data

Model No.	Max. Load* (pounds)	Spring Rate (pounds/Inch)	Model No.	Max. Load* (pounds)	Spring Rate (pounds/Inch)	Model No.	Max. Load* (pounds)	Spring Rate (pounds/Inch)
HDS-427 HDIS-427	2800	2240	HDS-627 HDIS-627	4200	3360	HDS-827 HDIS-827	5600	4480
HDS-428 HDIS-428	4160	4380	HDS-628 HDIS-628	6240	6570	HDS-828 HDIS-828	8320	8760
HDS-429 HDIS-429	5572	7432	HDS-629 HDIS-629	8358	11148	HDS-829 HDIS-829	11144	14864
HDS-475 HDIS-475	7600	11544	HDS-675 HDIS-675	11400	17316	HDS-875 HDIS-875	15200	23066
HDS-527 HDIS-527	3500	2800	HDS-727 HDIS-727	4900	3920	HDS-927 HDIS-927	6300	5040
HDS-528 HDIS-528	5200	5475	HDS-728 HDIS-728	7280	7665	HDS-928 HDIS-928	9360	9855
HDS-529 HDIS-529	6965	9290	HDS-729 HDIS-729	9751	13006	HDS-929 HDIS-929	12537	16722
HDS-575 HDIS-575	9500	14430	HDS-775 HDIS-775	13300	20202	HDS-975 HDIS-975	17100	25974

*For Loads Less than 2800 pounds, (1) or (2) spring isolators are available. Contact Factory.

✧ **“HDS” Series:** External Adjustment

✧ **“HDIS” Series:** Internal Adjustment



SWISSCO SYSTEMS