

# HDS Seismic Isolator Series

**LOAD RANGE:** Up to 20500 pounds

***General Purpose Seismic Series:  
For Zone 1 through 4 Seismic Applications***

## General Characteristics

- ✓ Heavy-Duty Steel Housing, Engineered and Independently Certified for Seismic Zones 1 through 4 – Standard
- ✓ Total Seam-Welded Construction – Standard
- ✓ Sandblasted to White Steel, Primed & Finish-Coated Industrial Blue – Standard
- ✓ Zinc-Plated, Heavy-Duty Hardware – Standard
- ✓ External or Internal Level Adjustments – Standard
- ✓ Elastomer Sound Pads Cemented to Isolator Base – Available

## Springs

- ✓ Helically Coiled Springs, Manufactured to Rigid Specifications – Standard
- ✓ Manufactured from Oil-Tempered, High-Carbon Steel – Standard
- ✓ Color-Coded According to Load Range – Standard

## Snubbing and Anchoring

- ✓ All-Directional Snubbing Pads and Vertical Limit Stops – Standard
- ✓ Predrilled Anchor Base Plates – Standard
- ✓ Custom Drilling and Tapping on Top & Bottom Plates – Available

## Efficiency

- ✓ Load Ratings are GUARANTEED with Efficiencies Approaching 100%



**swissco systems**